



Waterproof Tape

Waterproof tape is an environment-friendly solvent-free sealing adhesive material, produced by blending butyl rubber with polyisobutylene and other raw materials.

Product features


- (1) Excellent mechanical properties: high bonding strength and tensile strength, good elasticity and elongation, and strong adaptability to interface deformation and cracking.
- (2) Stable chemical properties: excellent chemical resistance, weather resistance and corrosion resistance.
- (3) Reliable application performance: it has good adhesion, waterproof, sealing, low temperature resistance and follow-up, and good dimensional stability.
- (4) Operation is easy

Scope of application

- (1) Roof waterproofing, underground waterproofing, waterproof treatment of structural construction joints and lap sealing of polymer waterproof coiled materials for new projects.
- (2) Sealing and waterproof treatment of construction joints of subway tunnel structure in municipal engineering.
- (3) Airtight, waterproof and shock absorption at the joint of color profiled plate. Airtight, waterproof and shock absorption of joints in sunshine board project.
- (4) Bonding and sealing treatment in automobile assembly
- (5) Waterproof sealing treatment of joints in steel structure construction.
- (6) Butyl adhesive tape of composite aluminum foil is suitable for waterproof sealing of various civil roofs, color steel, steel structures, waterproof coiled materials, PC boards, etc. under sunlight.

Construction regulations

- (1) This regulation is applicable to the sealing and waterproof works of civil structure roof and metal plate surface using adhesive tape as waterproof coiled material bonding, metal profiled plate bonding, PC plate bonding and other supporting materials.
- (2) Construction shall be carried out within the temperature range of -35°C - 80°C (corresponding measures shall be taken when the specified temperature range is exceeded)
- (3) The surface of the base course must be cleaned or wiped clean and kept dry without floating soil and oil stain.

- 
- (4) The bonding part shall not be torn or stripped within 24 hours after construction.
- (5) Place the boxes on the floor about 10cm away from the ground. Do not stack more than 5 boxes.
- (6) Do not use it with waterproof materials containing organic substances such as benzene, toluene, methanol, ethylene and silica gel.

Size Data

Thickness (mm)	Width (cm)	Length (m)	Quantity Per Box (Roll)	Box Size (cm)	Net Weight Per Box
1	5	5	36	37*37*22	15
1	5	5	54	37*37*32	23
1	5	10	30	37*37*32	26
1	5	10	20	37*37*22	17
1	10	5	18	37*37*22	15
1	10	5	27	37*37*32	23
1	10	10	15	37*37*32	26
1	10	10	10	37*37*22	17
1	15	5	18	37*37*32	11
1	15	5	18	37*37*32	23
1	15	10	10	37*37*32	26
1	20	5	9	37*37*22	15
1	20	10	5	37*37*22	17